

LAST UPDATED: MARCH 05, 2021

FOAM20561A

Oil Foam Generating Stick

Product Overview

FOAM20561A is a surfactant for unloading gas wells. This product has good foaming properties in wells with greater than 75% condensate present in the fluid.

Recommended Applications

Product can be applied in batch applications for remedial treatment programs based on bulk fluid to be removed. The most common application is to shut-in the well and drop the stick in through a lubricator.

Features and Benefits

- Excellent for unloading oil wells.
- Condensate dispersible, water soluble stick containing surfactants that foam both condensate and water from gas-condensate wells.
- Product can tolerate high chloride concentrations.
- Convenient packaging and application.
- Cost effective.
- No bulk tanks or liquid injection systems required.

Feeding and Dosage

Dosage will vary depending on reservoir pressure. The number of sticks to be used is based on the volume of fluid above the perforations (approximately 8 to 17 sticks per barrel of fluid). Falling velocity is approximately 100 feet per minute, and the stick will dissolve within 30 to 80 minutes depending on temperature, salt content, and relative water motion. The sticks can be used independently or in conjunction with gas generating sticks. Consult Technical representatives or specialists for more details regarding specific treatment determinations and application procedures.

Shipping, Handling, and Storage

Read the label and Safety Data Sheet (SDS) for complete handling information before using or storing this product. product can be delivered in cases of 108 sticks. Sticks should be stored in a cool dry place. Observe normal precautions for industrial chemicals and keep away from heat, sparks, and open flames. Avoid contact with eyes and skin.

Physical Properties

Property	Value
Diameter	5/8 inches
Length	15 inches
Weight	2.9 oz / stick
Specific Gravity @ 20°C	1.08
Pour Point , °C	N/A - Solid
pH	N/A- Solid

Contact Information

If you need assistance or information, please call your ChampionX representative or visit www.championx.com

Safety and Environmental

Please refer to SDS for additional product details. In an emergency, please contact:
Chemtrc USA at 1-800-424-9300
Chemtrc Canada at 1-703-741-5970

Material Compatibility

For material compatibility, please refer to the ChampionX Preliminary Packaging Recommendation (PPR) or contact your local representative to obtain this information.

Disclaimer

The information provided in this Product Overview is correct to the best of our knowledge, information and belief at the date of its publication. The information given is intended to be only a general material overview and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.