



Nano Pro MT High Temp High Pressure Grease (Lithium Complex Base)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024
Issue date: 3/5/2025 Revision date: 3/5/2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : Nano High Temp High Pressure Grease (Lithium Complex Base)
Product code : NDT14GR, NDTLC35GR, NDTLC120GR, NDTLC400GR
Tariff Code : 2710.19.4000

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Lubricating grease. Consumer/Industrial Use.

1.4. Supplier's details

Manufacturer

Nano Pro MT
7427 Matthews-Mint Hill Road, Suite 201
Charlotte, NC 28227 - USA
T (877) 626-6776 or (704) 954-8290

1.5. Emergency phone number

Emergency number : CHEMTREC (800) 424-9300

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. Label elements

GHS US labeling

No labeling applicable

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

Not applicable



Nano Pro MT High Temp High Pressure Grease (Lithium Complex Base)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024
Issue date: 3/5/2025 Revision date: 3/5/2025 Version: 1.0

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Nonanedioic acid, dilithium salt	CAS-No.: 38900-29-7	1 - 5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon.
-------------	---

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--



Nano Pro MT High Temp High Pressure Grease (Lithium Complex Base)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024
Issue date: 3/5/2025 Revision date: 3/5/2025 Version: 1.0

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

For non-emergency personnel

No additional information available

For emergency responders

Environmental precautions : Prevent entry to sewers and public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:

Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing



Nano Pro MT High Temp High Pressure Grease (Lithium Complex Base)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024
Issue date: 3/5/2025 Revision date: 3/5/2025 Version: 1.0

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste. Gel. Semi-solid.
Color	: Red
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 150 °C / > 302 °F
Flammability (solid, gas)	: Not flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 1000 kg/m ³ @ 25 °C / 77 °F
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content : Not applicable

SECTION 10 Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials.



Nano Pro MT High Temp High Pressure Grease (Lithium Complex Base)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024
Issue date: 3/5/2025 Revision date: 3/5/2025 Version: 1.0

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

Nano High Temp High Pressure NXD Grease (Lithium Complex Base)

Viscosity, kinematic	No data available
----------------------	-------------------

Nonanedioic acid, dilithium salt (38900-29-7)

Viscosity, kinematic	No data available
----------------------	-------------------

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

12.2. Persistence and degradability

Nano High Temp High Pressure NXD Grease (Lithium Complex Base)

Persistence and degradability	Not established.
-------------------------------	------------------



Nano Pro MT High Temp High Pressure Grease (Lithium Complex Base)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024
Issue date: 3/5/2025 Revision date: 3/5/2025 Version: 1.0

Nonanedioic acid, dilithium salt (38900-29-7)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

12.3. Bioaccumulative potential

Nano High Temp High Pressure NXD Grease (Lithium Complex Base)

Bioaccumulative potential	Not established.
---------------------------	------------------

Nonanedioic acid, dilithium salt (38900-29-7)

Partition coefficient n-octanol/water	-3.3 (at 20 °C (for Azelate; at pH 7)
---------------------------------------	---------------------------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No
Other information : No other effects known.

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14 Transport information

In accordance with DOT

14.1. UN number

UN-No.(DOT) : Not regulated

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Not regulated

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not regulated

14.4. Packing group

Packing group (DOT) : Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable



Nano Pro MT High Temp High Pressure Grease (Lithium Complex Base)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024
Issue date: 3/5/2025 Revision date: 3/5/2025 Version: 1.0

14.7. Special precautions for user

Not applicable

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

No additional information available

15.3. State regulations

WARNING: This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.


SECTION 16 Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Revision date : 3/5/2025
Issue date : 3/5/2025
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



NFPA health hazard : 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.