

High Temperature/High Strength Magnet

The High Temperature/High Strength Magnet is used to recover loose ferrous objects from within a well.

Unlike normal magnets, the Peak magnetic insert can withstand prolonged exposure to very high downhole temperatures without losing magnetic strength.

APPLICATIONS

- Recovery of ferrous objects such as parted pulling tool dogs, perforating gun debris, corrosion scale, etc.

FEATURES AND BENEFITS

- Rated for extreme high-temperature
- Suitable for oil and gas environments with high resistance to CO₂ and H₂S
- Ensured recovery of ferrous objects with powerful magnetic insert
- Available in a range of sizes to suit application and well geometry
- Effective conveyance into the well enabled by stainless steel shroud
- Customized magnet designs available

MAGNETIC PERFORMANCE TABLE

Contact Point	Magnet Assembly OD, in					
	1.750	2.220	2.720	3.500	3.750	4.500
1 ⁵ / ₁₆ -in SR Thread	140 lbm	210 lbm	235 lbm	250 lbm	250 lbm	275 lbm
1 1 ⁵ / ₁₆ -in SR Thread	175 lbm	245 lbm	265 lbm	300 lbm	300 lbm	320 lbm
1 1 ¹ / ₂ -in UN Thread	100 lbm [†]	230 lbm [†]	380 lbm	460 lbm	460 lbm	500 lbm
2-in UN Thread	N/A	150 lbm [†]	345 lbm [†]	565 lbm	565 lbm	650 lbm

[†] Magnet stands off contact point so full face contact is not made.

TECHNICAL INFORMATION

Actual OD, in [mm]	Temperature Rating, degF [degC]
1.750 [44.4]	500 [260]
2.220 [56.4]	500 [260]
2.720 [69.1]	500 [260]
3.500 [88.9]	500 [260]
3.750 [95.2]	500 [260]
4.500 [114.3]	500 [260]
5.500 [139.7]	500 [260]



▲ High Temperature/High Strength Magnet

Product Code: High Temperature/High Strength Magnet / 115

info@peakwellsystems.com | peakwellsystems.com

© 2021 Peak Well Systems Pty Ltd. All rights reserved. Revision: 10 August 2021

