

Spang Jar

The Spang Jar generates impact force required downhole to manipulate tools and sever shear pins.

Jar impact is mainly affected by speed of movement, applied stem weight above the jar, stroke length, and deviation. Peak Spang Jars are available in various stroke lengths, diameters, and connection options to suit the customers requirements.

APPLICATIONS

- Provide upward and downward impact in conjunction with the toolstring weight and wireline speed

FEATURES AND BENEFITS

- Supplied in a range of sizes and stroke lengths to suit most application
- Offered with available third-party proprietary connections to suit customer requirements

TECHNICAL INFORMATION		
Tool OD, in [mm]	Stroke, in [cm]	Fish Neck, in [mm]
1.250 [31.8]	20 [50.8] or 30 [76.2]	1.187 [30.1]
1.500 [38.1]	20 [50.8] or 30 [76.2]	1.375 [34.9]
1.750 [44.4]	20 [50.8] or 30 [76.2]	1.375 [34.9]
1.875 [47.6]	20 [50.8] or 30 [76.2]	1.750 [44.4]
2.125 [54]	20 [50.8] or 30 [76.2]	1.750 [44.4]
2.500 [63.5]	20 [50.8] or 30 [76.2]	2.313 [58.8]



All standard industry connections available



Spang Jar in closed (left), open (right) states.

Product Code: Spang Jar / 127

info@peakwellsystems.com | peakwellsystems.com

© 2021 Peak Well Systems Pty Ltd. All rights reserved. Revision: 10th August 2021

