


DESCRIPTION: SIZE 5-1/2, 14-20# x 2-7/8, 6.5# MECHANICAL SET RETRIEVABLE PACKER WITH EU BOX (UP) x PIN (DOWN) THREAD

DATE: 10/02/2021

REV. NO.: 00



NOTE: ALL DIMENSIONS ARE IN INCHES.

PREPARED BY.- VISHAL

REVIEWED BY.- SANDEEP

APPROVED BY.- BIBHU

PAGE.- 1 OF 2

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF SAZ AND MAY NOT BE REPRODUCED IN ANY FORM EITHER WHOLE OR IN PART OR DISTRIBUTED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF SAZ. MAKES NO REPRESENTATION AS TO THE ACCURACY OF THIS DOCUMENT.

SAZ OIL FIELD

DESCRIPTION: SIZE 5-1/2, 14-20# x 2-7/8, 6.5# MECHANICAL SET RETRIEVABLE PACKER WITH EU BOX (UP) x PIN (DOWN) THREAD

DATE: 10/02/2021

REV. NO.: 00

PRODUCT TECHNICAL SPECIFICATION

PRODUCT NO.	MSPOMIX5.5-50
PRODUCT NAME	MECHANICAL SET RETRIEVABLE PACKER
PRODUCT TYPE	RETRIEVABLE TYPE
PRODUCT CHARACTERISTIC	PRODUCTION / ISOLATION PACKER
SERVICE CLASS	STANDARD / SOUR SERVICE
METALLIC MATERIAL	AISI 4140 18-22HRC OR EQUIVALENT 80 KSI (L-80 TYPE 1)
NON-METALLIC MATERIAL	HNBR 90-80-90 DURO
DRIFT DIAMETER	4.653"
GAUGE OD/MAX OD (B)	4.610"
O.A LENGTH	85.30 "
RATED MAX TEMPERATURE	275°F
TEMPERATURE CYCLE RANGE	100°F - 275 °F
RATED PERFORMANCE ENVELOPE (POE)	YES
PACKER DIFFERENTIAL PRESSURE RATING	10000 PSI
PACKER BODY BURST PRESSURE RATING	N/A
TOP CONNECTION	2-7/8" - 8 RD - 3/4 TPF EU BOX (REF. DWG)
BOTTOM CONNECTION	2-7/8" - 8 RD - 3/4 TPF EU PIN (REF. DWG)
CASING SIZE	5-1/2"
CASING PPF RANGE	14-20 PPF
CASING ID RANGE (SETTING ID)	5.012" - 4.778"
TUBING SIZE	2-7/8"
TUBING PPF	6.5 PPF
TUBING ID / MIN ID (A)	2.375"
CONVENYENCE METHOD	BY TUBING CONDUIT
MAX. CONVENYANCE OD THROUGH TOOL	2.250" MAX OD INCLUDING FOR RT/REPOSITIONING TOOLS
MAX. CONVENYANCE OD THROUGH CASING	N/A
SETTING METHOD	1/4 TRUN RIGHT HAND ROTATION SET-DOWN WEIGHT MECHANICAL SET
RETRIEVING METHOD	1/4 TRUN RIGHT HAND ROTATION STRAIGHT PULL
REPOSITIONING METHOD	NOT APPLICABLE (NO REPOSITIONING RECOMMENDED)
QUALITY GRADE	N/A
VALIDATION GRADE	N/A
OPERATIONAL MANUAL REFERENCE NO.	SAZ/DES/OM-013
APPLICABLE REF. STANDARD	API 11D1 3RD ED
COMPLETE SETTING FORCE (LBS)	7000 +/-10%
RELEASING FORCE(LBS)	N/A
RUNNING IN HOLD ESPEED	3 FPS
MAX. ALLOWABLE CIRCULATION RATE THROUGH THE PACKER	N/A

NOTE: ALL DIMENSIONS ARE IN INCHES.

PREPARED BY.- VISHAL

REVIEWED BY.- SANDEEP

APPROVED BY.- BIBHU

PAGE.- 2 OF 2

THIS DOCUMENT IS THE CONFIDENTIAL PROPERTY OF SAZ AND MAY NOT BE REPRODUCED IN ANY FORM EITHER WHOLE OR IN PART OR DISTRIBUTED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF SAZ. MAKES NO REPRESENTATION AS TO THE ACCURACY OF THIS DOCUMENT.